



# Sidewinder<sup>®</sup> Bender

For Rigid, EMT, IMC and PVC conduit

**Bend Angle Gauge**  
Accurate bending results

**Pivoting, Compact Handle**  
Facilitates offset bends

**Rugged Drive Mechanism**  
Long lasting  
and dependable

**Interchangeable Shoes  
and Rollers**  
Compatible with  
Greenlee, Current  
and Ensley Benders

**Durable 10" Tires**  
Increased mobility on  
the jobsite

**Durable Frame Construction**  
Strong and long lasting



**Limited  
Two Year  
Warranty**

Introducing a conduit bender that is as easy-to-use as it is flexible. With interchangeable shoes and rollers for rigid, EMT, IMC and PVC conduit, the Sidewinder<sup>®</sup> offers versatility without sacrificing durability. Compatible with competitors' shoes and rollers, the Sidewinder<sup>®</sup> is a smart investment to increase jobsite productivity.

# Sidewinder<sup>®</sup> Bender



Easy-to-Change Shoes



Rugged and Dependable Mechanical Drive

## Versatility

The Sidewinder<sup>®</sup> Bender product line offers solutions for bending ½" through 2" rigid, EMT, IMC and 40 mil PVC conduit. Start with the Sidewinder<sup>®</sup> base unit and add the shoes and rollers you need, or choose one of the four models specific to conduit type. Either way, Sidewinder<sup>®</sup> is a cost-effective solution that you can build on for a wide range of applications.

## Compatibility

Shoes and rollers from other companies are no problem for the Sidewinder<sup>®</sup>! Greenlee's 555, Current's 77 and Ensley's E-969 assemblies slide right onto the Sidewinder<sup>®</sup> to maximize your equipment investment.

## Portability

Big, tough 10" tires make moving the Sidewinder<sup>®</sup> no problem at all. Streamlined, out-of-the-way handles aid maneuverability and pivot to facilitate offset "dogleg" bends.

## Durability

Depend on the Sidewinder<sup>®</sup>'s rugged, dependable motor and mechanical drive to make thousands of bends without fail! Make 180° bends on conduit as large as 2" in diameter. Simple relay control facilitates easy field repairs. Two year limited warranty.



## Centerline Radius Chart

Nominal Size	EMT	IMC	Rigid
½"	4¼"	4¾"	4¾"
¾"	5¾"	4½"	4½"
1"	6¾"	5¾"	5¾"
1¼"	8¾"	7¼"	7¼"
1½"	8¾"	8¾"	8¾"
2"	9¾"	9¾"	9¾"

Part #	Description	Capacity / Range
B2555	B2255 Electric Sidewinder <sup>®</sup> w/o Shoes	n/a
B2555RIG	B2255 Electric Sidewinder <sup>®</sup> w/ Rigid Shoe Group	½"-2" Rigid conduit and ½"-1¼" IMC conduit
B2555EMT	B2255 Electric Sidewinder <sup>®</sup> w/ EMT Shoe Group	½" - 2" EMT conduit
B2555IMC	B2255 Electric Sidewinder <sup>®</sup> w/ IMC Shoe Group	1½" - 2" IMC conduit
B2555PVC	B2255 Electric Sidewinder <sup>®</sup> w/ PVC Shoe Group	½" - 2" 40 mil PVC coated conduit