

GTB-406 & GTB-408 Double Row Terminal Blocks

DS-0018

Series GTB-406 & GTB-408 Double Row Terminal Blocks

SPECIFICATIONS

Rating: GTB-406 – 45A, 600V*
GTB-408 – 30A, 600V*

Center Spacing: .562" or 9/16" (14.28 mm)

Wire Range: #8-#22 AWG CU

Screw Size: GTB-406 – #10-#32 philslot screws
GTB-408 – #8-#32 philslot screws

Torque Rating: #8 screws – 16 in.-lb.; #10 screws – 20 in.-lb.

Distance Between Barriers: .41" (10.5 mm)

Mounting: GTB-406 – #10 screws; GTB-408 – #8 screws

Operating Temperature: 130 °C (226 °F) max., -40 °C (-40 °F) min.

Material: Molded base: Black, UL rated 94V0 thermoplastic
Terminal plating: Tin over brass; Screws: Zinc plated steel

Breakdown Voltage: 7500V

Agency Information: UL/CSA; IEC Compliance; CE Certified

* Max. rating shown; some options may be rated lower - consult factory.



GTB-408



GTB-406

Poles	A (inches)	B (inches)
02	2.13	1.69
03	2.69	2.25
04	3.25	2.81
05	3.81	3.37
06	4.37	3.94
07	4.94	4.50
08	5.50	5.06
09	6.06	5.62
10	6.62	6.19
11	7.18	6.75
12	7.75	7.31
13	8.31	7.87
14	8.87	8.44
15	9.43	9.00
16	9.99	9.56
17	10.56	10.12
18	11.12	10.68
19	11.68	11.25
20	12.24	11.81
21	12.80	12.37
22	13.37	12.93
23	13.93	13.50
24	14.49	14.06

Dimensions in inches. To convert to millimeters, multiply by 25.4.

