

## All New Cable Grips

Gardner Bender offers a complete line of cable pulling grips that complement a rich line of high quality fishing and pulling products. All of the grips are constructed from galvanized steel to add durability and resist corrosion.




### Junior Basket-Type Pulling Grip




- 340–820 lbs maximum rated capacity
- Ideal for small job requirements
- Single weave of galvanized steel mesh
- For use in conduit or cable tray
- Flexible pulling eye

### T-Basket-Type Pulling Grips (short mesh length)



- 900–6,200 lbs maximum rated capacity
- Ideal for medium-duty applications
- Double weave of galvanized steel mesh
- For use in conduit, tray, overhead, or underground
- Flexible pulling eye

### T-Basket-Type Pulling Grips



- 1,360–6,200 lbs maximum rated capacity
- Ideal for medium-duty applications
- Double weave of galvanized steel mesh
- For use in conduit, tray, overhead, or underground
- Flexible pulling eye

### K-Basket-Type Pulling Grips



- 1,120–9,600 lbs maximum rated capacity
- Ideal for long, heavy-duty cable pulls
- Double weave of galvanized steel mesh
- For use in conduit, tray, overhead, or underground
- Forged steel compact rotating eye



Part #	Description	Max. Rated Capacity (lbs)	Cable / Bundle Diameter Range											
			.25-.36" (6.4-9.1 mm)	.37-.49" (9.4-12.4 mm)	.50-.61" (12.7-15.5 mm)	.62-.74" (15.7-18.8 mm)	.75-.99" (19.1-25.1 mm)	1.00-1.24" (25.4-31.5 mm)	1.25-1.49" (31.8-37.8 mm)	1.50-1.99" (38.1-50.0 mm)	2.00-2.49" (50.8-63.2 mm)	2.50-2.99" (63.5-75.9 mm)	3.00-3.49" (76.2-88.6 mm)	3.50-3.99" (88.9-101.3 mm)
<b>JUNIOR BASKET-TYPE PULLING GRIPS</b>														
Light Duty Pulling (80-780 lbs)	PGJ-025	.25-.36" (6.4-9.1 mm)	340	■										
	PGJ-037	.37-.49" (9.4-12.4 mm)	340		■									
	PGJ-050	.50-.61" (12.7-15.5 mm)	340			■								
	PGJ-062	.62-.74" (15.7-18.8 mm)	560				■							
	PGJ-075	.75-.99" (19.1-25.1 mm)	820					■						
	PGJ-100	1.00-1.24" (25.4-31.5 mm)	820						■					
<b>T-BASKET-TYPE PULLING GRIPS (SHORT)</b>														
Medium Duty Pulling, Short Mesh Length (900-6,200 lbs)	PGTS-050	.50-.61" (12.7-15.5 mm)	900			■								
	PGTS-062	.62-.74" (15.7-18.8 mm)	1,120				■							
	PGTS-075	.75-.99" (19.1-25.1 mm)	1,360					■						
	PGTS-100	1.00-1.49" (25.4-37.8 mm)	1,920						■					
	PGTS-150	1.50-1.99" (38.1-50.0 mm)	3,280							■				
	PGTS-200	2.00-2.49" (50.8-63.2 mm)	3,700								■			
	PGTS-250	2.50-2.99" (63.5-75.9 mm)	4,900									■		
	PGTS-300	3.00-3.49" (76.2-88.6 mm)	4,900										■	
	PGTS-350	3.50-3.99" (88.9-101.3 mm)	6,200											■
<b>T-BASKET-TYPE PULLING GRIPS (STANDARD)</b>														
Medium Duty Pulling, Standard Mesh Length (1,360-6,200 lbs)	PGT-075	.75-.99" (19.1-25.1 mm)	1,360					■						
	PGT-100	1.00-1.49" (25.4-37.8 mm)	1,920						■					
	PGT-150	1.50-1.99" (38.1-50.0 mm)	3,280							■				
	PGT-200	2.00-2.49" (50.8-63.2 mm)	3,700								■			
	PGT-250	2.50-2.99" (63.5-75.9 mm)	4,900									■		
	PGT-300	3.00-3.49" (76.2-88.6 mm)	4,900										■	
<b>K-BASKET-TYPE PULLING GRIPS</b>														
Heavy Duty Pulling, Long Runs, Swivel Head (1,120-9,600 lbs)	PGK-050	.50-.61" (12.7-15.5 mm)	1,120		■									
	PGK-062	.62-.74" (15.7-18.8 mm)	1,360			■								
	PGK-075	.75-.99" (19.1-25.1 mm)	1,920				■							
	PGK-100	1.00-1.49" (25.4-37.8 mm)	3,280					■						
	PGK-150	1.50-1.99" (38.1-50.0 mm)	3,280						■					
	PGK-200	2.00-2.49" (50.8-63.2 mm)	5,440							■				
	PGK-250	2.50-2.99" (63.5-75.9 mm)	6,600								■			
	PGK-300	3.00-3.49" (76.2-88.6 mm)	8,200									■		
	PGK-350	3.50-3.99" (88.9-101.3 mm)	9,600										■	
PGK-400	4.00-4.49" (101.6-114.0 mm)	9,600											■	

## WHEN PULLING BUNDLES OF CABLE:

Where the Cable Diameter is Known:

INDIVIDUAL CABLE DIAMETERS Number of Cables in Each Grip				GRIP DIAMETER
2	3	4	5	Range
.30-.38	.25-.31	.22-.27	.19-.24	.50-.61
.38-.44	.31-.36	.27-.31	.24-.29	.62-.74
.44-.59	.36-.49	.31-.42	.29-.38	.75-.99
.59-.75	.49-.63	.42-.54	.38-.48	1.00-1.24
.75-.90	.63-.76	.54-.65	.48-.58	1.25-1.49
.90-1.07	.76-.89	.65-.77	.58-.67	1.50-1.74
1.07-1.22	.89-1.02	.77-.88	.67-.77	1.75-1.99
1.22-1.53	1.02-1.28	.88-1.10	.77-.96	2.00-2.49
1.53-1.83	1.28-1.53	1.10-1.32	.96-1.16	2.50-2.99
1.83-2.14	1.53-1.79	1.32-1.54	1.16-1.35	3.00-3.49
2.14-2.44	1.79-2.05	1.54-1.76	1.35-1.54	3.50-3.99
2.44-2.75	2.05-2.30	1.76-1.98	1.54-1.74	4.00-4.49
2.75-3.06	2.30-2.56	1.98-2.20	1.74-1.93	4.50-4.99

Where the Cable Diameter is Not Known:

CIRCUMFERENCE RANGE (inches)	GRIP DIAMETER RANGE (inches)
1.57-1.95	.50-.61
1.95-2.36	.62-.74
2.36-3.14	.75-.99
3.14-3.93	1.00-1.24
3.93-4.71	1.25-1.49
4.71-5.50	1.50-1.74
5.50-6.28	1.75-1.99
6.28-7.85	2.00-2.49
7.85-9.42	2.50-2.99
9.42-11.00	3.00-3.49
11.00-12.57	3.50-3.99
12.57-14.14	4.00-4.49
14.14-15.71	4.50-4.99

